

AT-1 Clear Very High Bond Acrylic Tape

Product Data Sheet

ADCO AT-1 is a pressure sensitive, water-clear, solid acrylic tape system designed to provide a superior bond between a wide variety of substrates. Because of its transparent appearance, ADCO AT-1 is often used in adhesive applications involving glass or other clear materials. The tape possesses a uniform high-tack acrylic adhesive on both surfaces and will bond to most clean, dry, oil-free substrates. The tape is formulated to withstand a wide range of weathering and temperature conditions without losing adhesion.

ADCO AT-1 can be used in a variety of applications including auto trim attachment, signs, graphics, skin to frame assembly, furniture, appliances, and many other manufacturing and construction applications to replace mechanical fasteners and welds. ADCO AT-1 offers numerous advantages including a waterproof bond, ease of application, the ability to withstand thermal movement, and sound deadening properties.

ADVANTAGES

- Pressure sensitive bonding
- Stain resistant after aged contact
- Solid composition for easy cutting
- Moisture resistant
- Excellent weathering properties
- Reduces and dampens vibration and shock
- Maintains adhesion at sub-zero temperatures

and safety measures are indicated herein or that other measures may not be required. 10/01

- Hardening or brittle resistant with age
- Flexible, moldable, compressible conforms to intricate shapes

TECHNICAL DATA



Tape Color		Clear
Tape Thickness		0.010, 0.020, 0.025, 0.030", 0.040, and 0.060 in.
		0.254, 0.508, 0.635, 0.762, 1.016, and 1.524mm
Tape Width		0.25 - 18 in.
		6.35 – 457.2mm
Tensile Strength	ASTM D412 Die C	150 psi
		0.1054 kg/mm2
Elongation	ASTM D412 Die C	1000%
Peel Adhesion	ASTM D3330	10 pli
		1.751 NLMM
Cleavage Peel Strength	ASTM D1062	20 psi
		0.0141 kg/mm2
Dynamic Shear Strength	ASTM D3163	60 psi
		0.0422 kg/mm2
Shelf Life		1 year
Installation Temperature		50°F – 100°F
		10°C – 37.8°C
Constant Temperature Limit		-30°F – 200°F
		-34.4°C – 93.3°C

Rev 8/2000

ISO 9001 REGISTERED OS 9000

ADCO Products, Inc. P.O. Box 457, 4401 Page Avenue Michigan Center, MI 49254 (800)248-4010 (517)764-6697 Fax

LIMITED WARRANTY: ADCO Products, Inc. ("ADCO") warrants its products to meet its published physical properties at the time of sale when tested according to ADCO's standards. If a product is proven to be defective, ADCO will, at its option, replace the defective product or refund the purchase price. ADCO shall not be liable for damages in excess of the purchase price. Any and all claims that a product is defective must be made in writing within thirty (30) days after discovery of the defect and in no event more than one (1) year after the original shipment of the product by ADCO. Failure to notify ADCO of any claim constitutes an irrevocable waiver of such claim regardless of the circumstances. THIS LIMITED WARRANTY IS THE USER'S SOLE AND EXCLUSIVE REMEDY (AND THE SOLE AND EXCLUSIVE LIABILITY OF ADCO) AND IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Notice: All statements and information in this publication are believed to be accurate and reliable as of the time of publication. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data