

TECHNICAL DATA SHEET

5001-042

PRODUCT DESCRIPTION

A low to medium tack masking tape for use in interior applications. The product consists of a self-wound polyethylene film in clear, blue or white coated with a custom formulated water based adhesive.

APPLICATIONS

Ideal for stainless steel sheets or coils of #3 or #4 finish as well as 2B. Excellent performance on matte or satin finished anodized aluminum and painted metals with low gloss or matte finish. Performs well in cut to length operations.

<u>PROPERTIES</u>		<u>US</u>	<u>Metric</u>	<u>Test Method</u>
Nominal Thickness		4.5 mils	114.3 μ	ASTM D3652
Adhesion		3.0 oz/in	33.5 g/cm	PSTC-1
Tensile	MD	3300 psi	231 kg/cm ²	ASTM D882
	TD	2700 psi	189 kg/cm ²	ASTM D882
Elongation	MD	500%	ASTM D882
	TD	850%	ASTM D882

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Main Tape assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Main Tape product proven defective. For full disclosure of the Limited Warranty, please contact your Main Tape Representative. 12/12