



A FLEXcon Holdings Company

Alamotape 210.798.1900
6110 Rittiman Road 800.549.9860
San Antonio, TX 78218 alamotape.com

TECHNICAL DATA SHEET

GP950 - Single-Coated Foam Tape Rubber PSA

Alamotape™ single-coated foam is an economical high-performance tape that combines high initial bond strength with excellent shear and cohesive strength.

Alamotape 's GP950 is designed as a cost-effective, general purpose adhesive foam pad suitable for use in gaskets, anti-skid and vibration dampening pads. The synthetic rubber adhesive bonds well to a wide variety of materials, including many plastics. Cross-linked EVA:PE copolymer foam provides excellent mechanical strength for 1/32" and 1/16" tapes. Soft cross-linked PE foam is used in 1/8" and 1/4" tapes to provide better conformability to textured surfaces.

PRODUCT ATTRIBUTES

- Highly versatile
Bonds to a wide variety of substrates
Resists moderate levels of dust and dirt contamination
Not recommended for applications requiring high water resistance or prolonged exposure to sunlight
Not recommend for applications requiring high heat resistance

STANDARD SIZES AND COLORS

Table with 4 columns: THICKNESS, WIDTH, LENGTH, COLOR. Rows include 1/32", 1/16", and 1/8" thicknesses with 60" width and lengths of 216', 108', and 70'.

\*Custom sizes are available upon request.

REPRESENTATIVE PHYSICAL PROPERTIES

Table with 3 columns: PROPERTY, VALUE (1/16" FOAM), TEST METHOD. Rows include DENSITY, TACK @72°F, PEEL ADHESION @72°F on SS, SHEAR ADHESION @72°F, and PRODUCT CONSTRUCTION details.

FT - Foam tears due to stronger adhesion A - Adhesive Failure C - Cohesive Failure NF - No Failure



A FLEXcon Holdings Company

Alamotape 210.798.1900  
 6110 Rittiman Road 800.549.9860  
 San Antonio, TX 78218 alamotape.com

**TECHNICAL DATA SHEET**

GAUGE	WIDTH (*)	LENGTH	COLORS		FOAM DENSITY			LINERS	
			WHITE	BLACK	2#	3#	5#	KRAFT	PE
1/32"	60"	216'	●	●			●	●	○
1/16"	60"	108'	●	●		●		●	○
3/32"	60"	108'	○	○		○		○	○
1/8"	60"	108'	●		●			●	○
3/16"	60"	108'	○	○	○			●	○
1/4"	60"	54'	○	○	○			○	○

● - Standard, ○ - Available Option / Minimum Quantity Requirement  
 (\*58" Usable)

**APPLICATION**

- Ensure that all surfaces are clean, dry and free from excessive dust prior to installation.
- Recommended application temperature is above 50°F (for lower temperature applications, contact Alamotape for additional information).
- Alamotape flame-retardant general-purpose tape in-service temperature range: -20°F to 150°F.

**STORAGE**

Shelf Life: one (1) year

Store in a clean area free from exposure to excessive heat, moisture or direct sunlight (45% to 55% relative humidity, 50°F to 80°F).

*Product performance will vary in each application and is dependent upon composite construction. Alamotape does not guarantee the replication of this data by third parties. None of the data or statements contained herein is intended to warrant the performance of this product. Data is representative and not intended as a manufacturing specification.*