

INDUSTRIAL GRADE CAULKING,
SEALANT AND ADHESIVE REMOVER

TECHNICAL DATA SHEET

RECOMMENDED FOR

- Silicone Sealants
- Polyurethane and Polysulfide Sealants and Adhesives
- Contact Adhesives
- Tape and Labels
- Tar, sap, and grease

SAFE ON

- Metals, including painted metals
- Glass and Mirrors
- Fiberglass
- Wood, including varnished and painted
- Stone, marble and tile
- Counter tops, including Formica and Corian
- Carpets and vinyl flooring
- Fabrics
- Most Plastics

DESIGNED FOR

DeGoop is designed to provide manufacturers and contractors with a safe, effective solvent for the easy removal of caulking and sealants including silicone, polyurethanes, polysulfides, silyl terminated polymers, contact adhesives, and tapes.

It is available in quart spray bottles, 5 gallon pails, and 55 gallon drums.

Product Description

Proprietary Blend of Petroleum Distillates and Distillates of Citrus

Appearance: Clear Liquid

Odor: Mild hydrocarbon

Relative Density: 0.76-0.79

Flash Point: 102°F

pH: 5.0-7.0

Initial Boiling Point and Boiling Range: 300-365°F

Stability and Reactivity:

Stability: Stable

Conditions to Avoid: Avoid heat, flame, and contact with strong oxidizing agents

Incompatible Materials: Strong Oxidizing Agents

Chemical Abstract Service Number (CAS)

Petroleum Distillates: 647-47-8/64742-9 <90%

Distillates of Citrus: 5989-27-5 < 15%

Shipping Data:

DOT Shipping Name: Petroleum Distillates, Liquid, N.O.S. III

DOT Hazard Class: 3